

## 丸鋼

外径	厚さ	単位重量	断面積	断面2次モーメント	断面係数	断面2次半径
48.6	2.4	2.73	3.483	9.32	3.83	1.64
	3.2	3.58	4.562	11.8	4.86	1.61
60.5	2.3	3.30	4.203	17.8	5.89	2.06
	2.8	3.98	5.073	21.2	7.00	2.04
	3.2	4.52	5.76	23.7	7.84	2.03
76.3	2.8	5.08	6.462	43.7	11.5	2.6
	3.2	5.77	7.349	49.2	12.9	2.59
89.1	3.2	6.78	8.636	79.8	17.9	3.04
	3.5	7.39	9.412	86.4	19.4	3.03
	4.2	8.79	11.2	101	22.7	3.01
101.6	3.2	7.76	9.892	120	23.6	3.48
	3.5	8.47	10.79	130	25.6	3.47
	4.2	10.10	12.85	153	30.1	3.45
114.3	3.5	9.56	12.18	187	32.7	3.92
	4.5	12.2	15.52	234	41.0	3.89
139.8	4.0	13.4	17.06	394	56.3	4.8
	4.5	15.0	19.13	438	62.7	4.79
165.2	4.5	17.8	22.72	734	88.9	5.68
	5.0	19.8	25.16	808	97.8	5.67
190.7	5.3	24.2	30.87	1,330	139	6.56
216.3	5.8	30.1	38.36	2,130	197	7.45
	8.2	42.1	53.61	2,910	269	7.36
267.4	6.6	42.4	54.08	4,600	344	9.22
	9.3	59.2	75.41	6,290	470	9.13
318.5	6.9	53.0	67.55	8,200	515	11.0
	10.3	78.3	99.73	11,900	744	10.9
355.6	6.4	55.1	70.21	10,700	602	12.3
	7.9	67.7	86.29	13,000	734	12.3
	11.1	94.3	120.1	17,800	1,000	12.2
406.4	6.4	63.1	80.42	16,100	792	14.1
	7.9	77.6	98.9	19,600	967	14.1
	9.5	93.0	118.5	23,300	1,150	14.0
457.2	12.7	123.0	157.1	30,500	1,500	13.9
	6.4	71.1	90.64	23,000	1,010	15.9
	9.5	105.0	133.6	33,500	1,470	15.8
	12.7	139.0	177.3	43,800	1,920	15.7